


Oxford[®]



Mobile Hoists



 **Joerns**
Healthcare

Redefining patient handling

Oxford Mobile Hoists



Offering the widest range of mobile lifters on the market, Oxford is your ideal partner for domestic, nursing or institutional settings. Oxford hoists are the leading patient handling specialists with over 30 years experience.

Whether a product specifier, user or servicing agent, our range of mobile hoists has been meticulously designed with you in mind.

Your complete range of mobile patient lifts

Mini 140

The Oxford Mini 140 and Stowaway 140 folding hoist have been developed especially with the domestic care environment and patient in mind. These compact but highly durable lifters offer superb manoeuvrability around the confines of both domestic and nursing settings. Both hoists offer an excellent range of minimum and maximum lift heights, as well as having durable low profile front castors for that all important lift from the bed or chair.

The Mini and Stowaway are available in both electric and hydraulic versions.



Mini 140 (140 kgs SWL)



Stowaway 140 (140 kgs SWL)

Stowaway 140



Stowaway:
Folded for easy storage



Linak battery & actuator



Control box
with LCD display



Easy to use hand control



Off-board
desktop charger



Emergency descent

Midi 170

The Oxford Midi 170 has become the versatile industry standard in homecare, offering surprising performance for a hoist of its size. The Oxford Midi offers the perfect solution for the community/nursing environment, whilst being sympathetic to the space constraints it may encounter. Available in both electric and hydraulic versions, the Midi is the all-round performer.



Midi 170 (170 kgs SWL)



Major 190 (190 kgs SWL)

Major 190

The Oxford Major 190 is a true heavyweight contender and is the perfect cross over product for both nursing and institutional care. Its high lifting capacity (190 kgs) and lightweight design allow the Major to work well in almost all settings.



75mm low profile castors



Sling attachment point



Hydraulic pump used on non-electric hoists



Leg opening device



Legs open wide for stable and safe lift

Maxi 170

The Oxford Maxi 170 is exceptionally versatile and with a maximum lift height from the floor of almost 2 metres, the Maxi can handle almost any patient handling task. The Maxi can lift patients onto almost all institutional and nursing surfaces. Remarkably, the Maxi maintains a relatively compact frame allowing the hoist to be manoeuvred and stored with ease.



Standaid 140 (140 kgs SWL)

Standaid 140

The Oxford Standaid 140 has a revolutionary patented design that enables patients to be quickly and efficiently transferred.

Unlike conventional passive sling lifters, the Standaid requires the patient to participate with the lift/transfer which clearly encourages the patient to remain active for as long as possible.

The Standaid hoist easily transfers patients from bed to chair or from chair to commode in a fraction of the time required for a conventional sling lifter. It is also a very useful rehabilitation tool.

The Standaid also provides an extremely secure and comfortable lift for those patients who have the upper body strength to participate. This is primarily due to the natural sitting position achieved by the lift mechanism and sling.



Maxi 170 (170 kgs SWL)



Standaid 140



Large knee pad for added support



Cow horn handles ensure a safe and stable transfer

Specification	Stowaway 140	Mini 140	Midi 170	Major 190	Maxi 170	Standard
Safe Working Load	140 kg (22 st)	140 kg (22 st)	170 kg (27 st)	190 kg (30 st)	170 kg (27 st)	140 kg (22 st)
Maximum Overall Length	1093 mm	1120 mm	1180 mm	1269 mm	1315 mm	1220 mm
Minimum Overall Length	1093 mm	1120 mm	1180 mm	1269 mm	1315 mm	1170 mm
Maximum Overall Height	1780 mm	1726 mm	1848 mm	1941 mm	2240 mm	1625 mm
Minimum Overall Height	1145 mm	1133 mm	1237 mm	1376 mm	1560 mm	1138 mm
Maximum Spreader Bar Height	1572 mm	1505 mm	1630 mm	1725 mm	1965 mm	-
Minimum Spreader Bar Height	500 mm	500 mm	495 mm	525 mm	755 mm	-
Spreader Bar Height at Maximum Reach	995 mm	986 mm	1070 mm	1110 mm	1351 mm	-
Spreader Bar Reach at Maximum Height	340 mm	340 mm	412 mm	589 mm	512 mm	-
Spreader Bar Reach at Minimum Height	505 mm	475 mm	480 mm	522 mm	533 mm	-
Maximum Height to Attachment Point	-	-	-	-	-	1585 mm
Minimum Height to Attachment Point	-	-	-	-	-	1090 mm
Maximum Reach	635 mm	595 mm	656 mm	754 mm	724 mm	240 mm
Turning Radius	1104 mm	1104 mm	1174 mm	1274 mm	1273 mm	1250 mm
Legs Open - External Width	1095 mm	1095 mm	1175 mm	1220 mm	1220 mm	1240 mm
Legs Open - Internal Width	1040 mm	1040 mm	1120 mm	1130 mm	1130 mm	1065 mm
Legs Closed - External Width	600 mm	600 mm	600 mm	640 mm	610 mm	610 mm
Legs Closed - Internal Width	540 mm	540 mm	500 mm	540 mm	540 mm	520 mm
Overall Height of Legs	140 mm	100 mm				
Ground Clearance	25 mm	25 mm	25 mm	127 mm	127 mm	30 mm
Front Twin Castors	75 mm					
Rear Braked Castors	100 mm					

Weights	Stowaway 140	Mini 140	Midi 170	Major 190	Maxi 170	Standard
Mast and Boom Assembly	-	17.5 kg	20.5 kg	23 kg	24 kg	18.5 kg
Base Assembly	-	11 kg	11.5 kg	19 kg	19 kg	30.0 kg
Total	28 kg	28.5 kg	32 kg	42 kg	43 kg	48.5 kg

Specifications may vary due to manufacturing tolerances

Electrical Specifications

Battery 1 X 12 volt rechargeable sealed lead acid type
 Battery capacity 3.2 Ampere hours
 Charger rated input 230Vac 50/60Hz
 Charger rated output 27.4/29.0 VDC@0.8A

Warranty

The Oxford mobile hoist range comes with a 12 month warranty as standard. Please refer to your user manual for further information.

Electrical Shock Protection

Charger - class II
 Lift - internal power source

Degree of shock protection
 Charger - Type B
 Lift - Type B
 Intended operating environment: >+5° <+40°
 Outside this environment functionality and safety may be compromised



Oxford®



Joerns Healthcare Limited
 High Street, Wollaston, Stourbridge, West Midlands DY8 4PS England
 (T) +44 (0)1384 446622 (F) +44 (0)1384 446601
 www.joerns.co.uk • email: info@joerns.co.uk